IS 11245: 2004

(Reaffirmed 2015)

(Reaffirmed 2020)

## भारतीय मानक वातिल सिलिंडर — क्रय विशिष्टि

( पहला पुनरीक्षण )

# Indian Standard PNEUMATIC CYLINDERS — PURCHASE SPECIFICATION

(First Revision)

ICS 23.100.20

© BIS 2004

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

#### **FOREWORD**

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Basic Fluid Power Sectional Committee had been approved by the Medical Instruments, General and Production Engineering Division Council.

In pneumatic fluid power systems power is transmitted and controlled through air or gas under pressure within a circuit. One component of such system is the fluid power cylinder. This is a device which converts piston power into linear mechanical force and motion. It consists of a movable element, that is a piston and piston rod, operating within a cylindrical bore.

This standard has been prepared to enable buyers to collect data as per their requirement from various manufacturers or suppliers for the purpose of comparison and subsequent collection.

This standard was first published in 1985. This revision has been made to bring the standard in line with the current practices prevalent in the industry as also to align it with the existing Indian Standards references of which are given in 2.

#### Indian Standard

### PNEUMATIC CYLINDERS — PURCHASE **SPECIFICATION**

(First Revision)						
1 SCOPE		IS No.	Title			
This standard specifies the purchasing data of pneumatic cylinders.		13087:1999	Pneumatic fluid power — Cylinders 1 000 kPa ( 10 bar )			
2 REFERENCES			series — Rod end clevis — Mounting dimensions ( first			
The following standards contain provisions, which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to			revision)			
		14167 : 1994	Pneumatic cylinders — Acceptance test			
revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below:		14645 : 1998	Fluid power systems and components—Cylinders—Nominal pressure			
IS No.	Title	3 DEFINITIONS				
8208 : 1976	Sizes for cylinder bores and piston rod diameter for fluid power systems	For the purpose of this standard, the definitions given in IS 10416 shall apply.				
10143:1995 Pneumatic fluid power — Single		4 SIZES				
	rod cylinder, 1 000 kPa (10 bar) series with detachable mountings, bores from 32 mm to 320 mm — Mounting dimensions (first revision)	4.1 Cylinder Bores				
		The cylinder bores shall be as per 3.1 of IS 8208.				
		4.2 Piston Rod Diameter				
10167:1982	Method for upsetting test on	The piston rod diameters shall be as per 3.2 of IS 8208.				
metallic materials		4.3 Piston Stroke				
10411 : 1983	Recommendations on nominal strokes for fluid power cylinder	The piston stro	ke(s) shall be as per 2.4 of IS 10411.			
10416:1992	Fluid power systems and	4.4 Mounting				
	components — Vocabulary ( first revision )	shall be made to	dimensions for cylinders, reference IS 10143, IS 12723, IS 12738, IS 13086			
12723 : 1988	Pneumatic fluid power — Single rod cylinder — 1 000 kPa (10 bar) series — Bores from 8 mm to	and IS 13087.				
		5 TESTING				

25 mm — Mounting dimensions

Pneumatic fluid power — Single rod cylinders, 1 000 kPa (10 bar)

series with integral mountings, bores from 32 mm to 250 mm —

Mounting dimensions ( first

Pneumatic fluid power — Cylinders

1 000 kPa ( 10 bar ) series — Rod

end spherical eyes - Mounting

dimensions (first revision)

revision)

12738:1995

13086:1999

For testing details of pneumatic cylinder, reference shall be made to IS 10167.

#### **6 NAME PLATE**

The cylinder shall be provided with a permanent name plate giving details as per A-15.

#### 7 PROFORMA FOR PURCHASE **SPECIFICATION**

Proforma for purchase specification may be in accordance with that given in Annex A.

Specify.

A-1 CYLINDER TYPE

#### ANNEX A

(Clauses 6 and 7)

#### PROFORMA FOR PURCHASE SPECIFICATION FOR PNEUMATIC CYLINDERS

Single acting/Double acting/Ram/Any other	
Push in/Push out/Bellow type	
Stroke adjustment: Yes/No	
Length of adjustment ( mm ):	•
A-2 PROXIMITY SENSING REQUIRED	
Yes/No	
A-3 SIZES (mm)	
BoreRodStrokeRam dia	<b>1</b>
A-4 RATINGS	
A-4.1 Pressure, kgf/cm <sup>2</sup> : Maximum working pressure	Rated pressure
A-4.2 Velocity, m/s: Maximum working speed	
A-4.3 Number of cycles/minute	
A-4.4 Temperature, °C : working temperature range: Mi	nMax
A-5 MOUNTING	
MF 8 Head rectangular flange ( two hole ) mounting	MX 1 Mounting with studs or tie rods extended a both ends
MP 3 Cap mounting, fixed eye	MP 1 Cap mounting, fixed clevis
MR 3 Head threaded mounting	MS 2 Mounting with side lugs
MS 3 Head angle mounting	MT 1 Head mounting, integral trunnion ( male )
MF 1 Head mounting, rectangular flange	MT 2 Cap mounting, integral trunnion ( male )
MF 2 Cap mounting, rectangular flange	MX 2 Cap mounting with studs or tie rods extended
MP 2 Cap mounting, detachable clevis	MX 3 Head mounting with tie rods extended
MP 4 Cap mounting, detachable eye	Rod end spherical eyes
MS 1 Mounting with end angles	Rod end clevis
MT 4 Mounting with intermediate fixed or movable trunnion (male)	Any other ( with dimensional drawing )
A-6 ROD END	
Eye/Thread/Clevis/Lock nut/Any other ( Specify )	
A-7 LOAD DETAILS	
A-7.1 Side load details, if any	
A-8 CUSHIONING AND DECELERATION DEVI	CES

2

A-9 ENVIRONMENTAL				
Acid vapour/Dust/Hard particles/Mud/Water/Snow/Tropical/Vibration/Molten metal/Any other	er			
A-10 PRIMER/PAINT				
Specify.				
A-10.1 Chemical Resistant Coating Required				
Yes/No. If yes, specify.				
A-11 SAFETY REQUIREMENTS				
Specify.				
A-12 SPECIAL REQUIREMENT				
Tolerance/Tracking/Accuracy, etc.				
A-12.1 Piston Rod Extension				
Yes/No. If yes, specify.				
A-13 TESTING REQUIREMENTS				
Specify — Functional test/Leakage test/Cushioning test for integrity/Any other test.				
A-14 SPACE CONSTRAINTS				
Yes/No. If yes, specify.				
A-15 NAME PLATE/PUNCHING/IDENTIFICATION DETAILS				
Type Bore Rod Stroke Working pressure  Port dimentions Overall length Manufacturer's reference number Year of manufacture Model label				
A-16 PACKAGING				
Specify.				
Signature of the purchaser				
Name of the purchaser				

Name and address of the company.....

#### **Bureau of Indian Standards**

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

#### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

#### Review of Indian Standards

MUMBAI 400 093

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc: No. MGP 14 (461).

#### **Amendments Issued Since Publication**

Amend No	Date of Issue	Text Affected
	BUREAU OF INDIAN STANDAR	DS
Headquarter	s:	
	an, 9 Bahadur Shah Zafar Marg, New Delhi 110 002 2323 0131, 2323 3375, 2323 9402 Website: www.bis.org.in	
Regional Of	fices:	Telephones
	lanak Bhavan, 9 Bahadur Shah Zafar Marg EW DELHI I 10 002	$ \begin{cases} 23237617 \\ 23233841 \end{cases} $
	/14 C. I. T. Scheme VII M, V. I. P. Road, Kankurgachi OLKATA 700 054	{ 2337 8499, 2337 8561 2337 8626, 2337 9120
Northern: S	CO 335-336, Sector 34-A, CHANDIGARH 160 022	$ \begin{cases} 2603843 \\ 2609285 \end{cases} $
Southern: C	. I. T. Campus, IV Cross Road, CHENNAI 600 113	{ 2254 1216,2254 1442 2254 2519,2254 2315
Western: M	lanakalaya, E9 MIDC, Marol, Andheri (East)	∫ 28329295,28327858

Branches: AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM. VISAKHAPATNAM.

[ 28327891,28327892